

EUROLITE LED KLS-180 Compact Light Set

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

Art. No.: 42109630

GTIN: 4026397599046



List price: 308.21 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Silent operation
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Flicker-free
- Preprogrammed in EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
- With Mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Application possibility: On stand

spotlight

- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 4 spots controlled separately

bar

- 4 powerful LEDs 1 W high-power cold white (CW)
 LEDs controlled separately

Package contents

- 1 x spotlight, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397599046

Weight: 5,50 kg

Length: 0.66 m

Width: 0.19 m

Height: 0.29 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,1 m
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
DMX channels:	3; 4; 8; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
Preprogrammed in:	EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 60,5 cm Depth: 14 cm Height: 23 cm
Weight:	4,85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Spotlight	
LED:	4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Bar	
LED:	4 x 1 W high-power cold white (CW)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting