

EUROLITE LED KLS-180 Compact Light Set wh

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

Art. No.: 42109635

GTIN: 4026397670066



List price: 332.01 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and stand sleeve
 - Compact lightweight
 - Movable and tiltable spotlights
 - With a beam angle of 9°
 - Dimmer electronic; color blend stepless; color change adjustable; colors preset
 - Strobe effect
 - Flicker-free
 - With Mounting bracket
 - Control via IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
 - Preprogrammed in EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
 - Mains input and output for power linking up to 8 units
 - Silent operation
 - Application possibility: Suspended; on stand
- spotlight**
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
4 spots controlled separately
- bar**
- 4 powerful LEDs 1 W high-power cold white (CW)
 LEDs controlled separately
- Package contents**
- 1 x device, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

Logistic

EAN / GTIN: 4026397670066
Weight: 5,65 kg
Length: 0.66 m
Width: 0.19 m
Height: 0.29 m

Technical specifications:

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 80 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Fuse: | T 1 A |
| Lamp type: | LED lamp |
| DMX channels: | 3; 4; 8; 21 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J |
| Projection: | Flicker-free |
| Beam angle: | 9° |
| Beam angle (1/2 peak): | 9° |
| Housing color: | White |
| Attachment system: | Mounting bracket |
| Dimensions: | Width: 60,5 cm Depth: 14 cm Height: 23 cm |
| Weight: | 5,10 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Spotlight | |
| LED: | 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Bar | |
| LED: | 4 x 1 W high-power cold white (CW) |
| Flash rate: | 1 - 20 Hz |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |