

EUROLITE LED KLS-902 Next Compact Light Set

Bar with 4 powerful RGB/WW spots, QuickDMX support, IR remote control and carrying bag

Art. No.: 42109860

GTIN: 4026397673166



List price: 570.01 €

incl. 19% VAT.

Features:

- 5 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix) spots controlled separately
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- With a beam angle of 16°
- 20 integrated show programs
- Color blend stepless; Dimmer electronic; program selection
- Mounting points and power outlets for additional fixtures
- Control via DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- For application areas such as: Mobile use; Stage; mobile djs / entertainer; small rental; Rental
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x omega bracket, 1 x declaration of conformity, 4 x knurled screw, 1 x bag

Logistic

EAN / GTIN: 4026397673166

Weight: 10,80 kg

Length: 1.13 m

Width: 0.38 m

Height: 0.18 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 125 W

IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A Fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A Fuse replaceable
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED:	5 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 1,08 m Depth: 6 cm Height: 28 cm
Weight:	9,80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting