

EUROLITE LED KLS-3002 Next Compact Light Set

Bar with 4 powerful RGBAW/UV spots, QuickDMX support, IR remote control and carrying bag

Art. No.: 42109895

GTIN: 4026397657654



List price: 712.81 €

incl. 19% VAT.

Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
 - 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) spots controlled separately
 - With a beam angle of 19°
 - 20 integrated show programs
 - Direct color selection for 21 preset colors
 - Dimmer electronic; color blend stepless; color selection; program selection
 - UV effect
 - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
 - For application areas such as: Mobile use; Stage; mobile djs / entertainer; Rental
 - Mounting points and power outlets for additional fixtures
 - Mains input and output for power linking up to 8 units
 - Silent operation
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x bag, 2 x omega bracket, 4 x knurled screw, 4 x washer, 1 x battery, 1 x terminating plug (power)

Logistic

EAN / GTIN: 4026397657654

Weight: 12,35 kg

Length: 1.32 m

Width: 0.15 m

Height: 0.39 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version fused 1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 2,5 A Fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	2; 4; 6; 10; 24; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	19°
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 1,28 m Depth: 8 cm Height: 29 cm
Weight:	11,14 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting