

EUROLITE Set 4x LED PARTY Spot Silent RGB/WW with Soft Bag

Compact spotlight with 12 x 5 W 4in1 QCL RGB/WW LED and DMX control

Art. No.: 42110204

GTIN: 4026397724882



List price: 284.41 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
 - Color blend stepless; color change programs; Dimmer electronic
 - Strobe effect
 - 10 integrated show programs
 - Direct color selection for 20 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light´J; Light Captain; LED PC-Control 512
 - Flicker-free
 - The article is delivered with practical transport bag
 - With a beam angle of 12°
 - With double bracket
 - 4 digit 7-segment LED display
 - 4 pieces per set
 - For application areas such as: Wedding/gala/events; party room; mobile djs / entertainer
 - Silent operation
- Package contents**
- 4 x device, 1 x user manual, 1 x remote control, 1 x battery, 1 x bag

Logistic

EAN / GTIN: 4026397724882

Weight: 2,90 kg

Length: 0.41 m

Width: 0.17 m

Height: 0.21 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	17 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0,75 mm² H03VVH2-F
Cable length:	Approx. 1 m
Device fuse:	T 1 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	12 x 5 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0,5 - 16 Hz
DMX channels:	4; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; LED PC-Control 512
Projection:	Flicker-free
PWM frequency:	2000 Hz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 9 cm Width: 15,5 cm Height: 19 cm Diameter: Ø 12,5 cm
Weight:	2,60 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	2 x Ø6mm; 1 x Ø13mm
Material:	Metal, 1,5 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting