eurolite®

EUROLITE LED Umbrella 95

Extraordinary RGB eye-catcher

GTIN: 4026397646061



The article is no longer in our assortment.

Features:

- 114 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
7 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light J; LED PC-Control 512; Light Captain
- Flicker-free
- Easy to assemble
- 3 digit 7-segment LED display
- For application areas such as: Advertisement/Shop window; Trade fair and shop fitting; clubs/dancing school; restaurants, bars and hotels; stage
- Application possibility: Suspended; on stand
- Package contents
- 1 x omega bracket, 1 x device, 1 x user manual, 1 x power cord, 1 x multipin cable, 1 x umbrella

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	10 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397646061 Weight: 3,90 kg Length: 0.80 m Width: 0.30 m Heigth: 0.24 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
LED type:	114 x SMD 5050 3in1 TCL RGB (homogenous color mix)
DMX channels:	6; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Setup:	Easy to assemble
Housing color:	Black
Display type:	3 digit 7-segment LED display
Weight:	2,68 kg
Umbrella	
Dimensions:	Diameter: Ø 95 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting