

EUROLITE LED MFX-8 Action Barrel

LED barrel, unlimited PAN/TILT movement, 15 W 4in1 LEDs in RGBW

Art. No.: 50944323

GTIN: 4026397592733



The article is no longer in our assortment.

Features:

- Beam effect with 9 lenses with 10 W quadcolor LEDs in RGBW colors arranged in 3 rows
- Compact lightweight
- With Infinity function for unlimited TILT movement
- Positioning within 630° PAN and 200° TILT
- PAN-angle switchable between 630° and 540°
- Functions: Colored beams, auto mode, color presets, color change, Master/Slave function, built-in programs, stepless RGBW color mixture - each LED row can be controlled individually
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- 9 powerful LEDs 10 W high-power 4in1 QCL RGBW
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect
- Control via DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light 'J
- Flicker-free
- With a beam angle of 9°

Logistic

EAN / GTIN: 4026397592733

Weight: 6,65 kg

Length: 0.39 m

Width: 0.32 m

Height: 0.21 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	9 x 10 W high-power 4in1 QCL RGBW
Max. TILT movement:	200° Exact positioning (16 bit resolution) plus infinity Auto position correction (feedback)
Max. PAN movement:	540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	0 - 25 Hz
DMX channels:	12; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	Black
Dimensions:	Width: 25,5 cm Depth: 13,5 cm Height: 32,5 cm
Weight:	5,95 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting