

ANTARI DarkFX Spot 1750

PRO DMX UV spot with 4 x 16 W UV LED, deep wavelength (365 nm)

Art. No.: 51100823

GTIN: 4719850658144



The article is no longer in our assortment.

Description:

The Antari DarkFX Spot 1750 is an efficient high-output and low-power consumption UV LED spot that delivers a peak wavelength of 365 nm and radiant flux output of 19,080 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors.

Equipped with 4 x 16 W high-power UV LEDs, it features a 20° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP20-rated LED spot comes with an aluminium housing with an adjustable bracket for versatile mounting options.

The DarkFX Spot 1750 is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

Features:

- Minimum visible light
- High output at full intensity
- Special optics will not degrade due to high UV exposure
- 4 powerful LEDs 16 W high-power ultra violet (UV)
- UV effect
- Control via stand-alone; DMX
- With a beam angle of 20°
- Built with NEUTRIK connector

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x mounting bracket, 2 x knurled screw, 4 x washer

Logistic

EAN / GTIN: 4719850658144

Weight: 3,85 kg

Length: 0.35 m

Width: 0.23 m

Height: 0.25 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	72 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	4 x 16 W high-power ultra violet (UV)
DMX channels:	2
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Control:	Stand-alone; DMX
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	44°
Wavelength:	365 nm
Housing color:	Black
Use of brands:	Built with NEUTRIK connector
Weight:	3,26 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting