

ANTARI F-5D Fazer

Silent fazer in flightcase with wireless DMX receiver

Art. No.: 51702676 GTIN: 4719850651848









The article is no longer in our assortment.

Features:

- Improved follow-up model of the F-3 with wireless DMX receiver and 200 % higher output
- Integration in a stackable flightcase makes the machine tough, durable and easy to carry
- Improved, even lower noise operation without air compressor ideal for theater and stage applications in silent environments
- Produces fine, translucent haze without nebulizing the room at the same time
- Ideal for accentuating light and laser beams
- Vertical and horizontal fog output possible
- Combines the reliability of a fog machine with the extremely silent operation of a haze machine
- Wireless DMX receiver (WDMX) for wireless data transmission with 2.4 GHz eliminates irksome cabling
- Due to AFHSS (Automatic Frequency Hopping Spread Spectrum) technology, interference-free operation also alongside other wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- Fluid consumption: 2 hours continuous output per liter
- Operates on standard waterbased fluid
- Removable tank
- Fan speed variably adjustable
- Self-cleaning function
- Control via integrated DMX interface or control module with LCD screen (functions: timer with interval, duration and output volume; continuous output; DMX starting address, fan speed, pump sensor)
- Intelligent wireless control system with 50 m range eliminates irksome cables
- PowerCon mains connector (cable included)
- Short warm-up time
- Operates on water-based fluid
- Control via W-DMX by wireless solution; stand-alone; DMX

Package contents

Logistic

EAN / GTIN: 4719850651848

Weight: 25,50 kg Length: 0.64 m Width: 0.57 m Heigth: 0.34 m - 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x container, 1 x tube

Technical specifications:

| <u> </u> | |
|--------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 900 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Warm-up time: | Approx. 4 min |
| Output volume: | Approx. 85 m³/min |
| Tank capacity: | 2,8 I water-based fluid |
| Fluid consumption: | Approx. 8 ml/min |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Control: | W-DMX by wireless solution; stand-alone; DMX |
| Housing color: | Black |
| Heater: | 800 W |
| Color: | Black |
| Dimensions: | Width: 48 cm Depth: 54 cm Height: 25 cm |
| Weight: | 23,10 kg |
| - | · |