

EUROLITE LED B-40 Laser Beam Effect wh

LED beam effect with RGBW color mixing and RG laser

Art. No.: 51741088

GTIN: 4026397666458



List price: 403.41 €

incl. 19% VAT.

Features:

- 2 laser diodes project hundreds of red and green laser beams
 - 5 powerful LEDs 8 W high-power 4in1 QCL RGBW
3 segments controlled separately
 - For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; Rental
 - Laser; multi beam effect; Strobe effect
 - Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
 - Rotation speed stepless; color blend stepless; Dimmer electronic
 - 7 integrated show programs
 - The device is cooled by cooling fan at the Head; cooling fan at the Base
 - Control via IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - With Mounting bracket
 - Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light`J
 - Mains input and output for power linking up to 8 units
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x mounting bracket, 4 x screw, 4 x washer

Logistic

EAN / GTIN: 4026397666458
Weight: 6,35 kg
Length: 0.39 m
Width: 0.39 m
Height: 0.49 m

Technical specifications:

| | |
|-----------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 65 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Fuse: | 5 x 20 mm, T 1 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 5 x 8 W high-power 4in1 QCL RGBW |
| Flash rate: | 0 - 20 Hz |
| Laser class: | 2M |
| Laser color: | R/G |
| Laser module: | Green (G) 40 mW 532nm Red (R) 100 mW 650nm |
| DMX channels: | 3; 10; 22 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan at the Head Cooling fan at the Base |
| Control: | IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J |
| Housing color: | White |
| Attachment system: | Mounting bracket |
| Dimensions: | Width: 31 cm Depth: 31 cm Height: 39 cm |
| Weight: | 4,30 kg |
| Noise classification: | Class 2 (slight noise) |