

EUROLITE LED KLS Laser Bar Next FX Light Set

Bar with powerful spots, UV strobe LEDs, laser (RG, 2M), QuickDMX port and carrying bag

Art. No.: 51741094 GTIN: 4026397684681











List price: 593.81 €

incl. 19% VAT.

Features:

- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- Compact lightweight
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- When fog is used, this effect becomes especially attractive
- Dimmer electronic; color blend stepless; program selection
- 26 integrated show programs
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- TV spigot
- With mounting bracket
- 3 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; clubs/dancing school; mobile djs / entertainer; small rental
- Application possibility: On stand

laser

- Laser
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer

spotlight

- 3 powerful LEDs 4 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
4 spots controlled separately
- With a beam angle of 7°

Logistic

EAN / GTIN: 4026397684681

Weight: 11,90 kg Length: 1.12 m Width: 0.20 m Heigth: 0.51 m

light effect

- 4 powerful LEDs 3 W SMD 8072 R/G/B/WW
 lighting effects controlled separately
- Multi beam effect; fan effect; flower effect

hai

- 4 powerful LEDs 1,5 W SMD 8072 ultra violet (UV)
 LEDs controlled separately
- UV effect; strobe effect

Package contents

1 x device, 1 x user manual, 1 x power cord, 1 x bag, 1 x declaration of conformity, 1 x remote control, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x terminating plug (power)

Technical specifications:

reclinical specifications.		
Power supply:	100-240 V AC, 50/60 Hz	
Power consumption:	90 W	
IP classification:	IP20	
Protection class:	Protection class I	
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)	
Cable length:	3 m	
Power output:	1 x P-Con (gray), mounting version	
Fuse:	T 1 A fuse replaceable	
Lamp type:	LED lamp	
DMX channels:	6; 8; 11; 21; 25; 29	
DMX input:	1 x 3-pin XLR (M) mounting version	
DMX output:	1 x 3-pin XLR (F) mounting version	
Cooling:	Cooling fan	
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)	
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief	
Housing color:	Black	
Attachment system:	TV spigot Ø 28mm	
	2x mounting bracket	
Display type:	3 digit 7-segment LED display	
Dimensions:	Width: 111 cm	
	Depth: 15 cm	
	Height: 41 cm	
Weight:	10,50 kg	
Noise classification:	Class 2 (slight noise)	
Remote control		
Battery:	Button cell 3.0 V CR2025 lithium manganese built in	
Laser		
Laser class:	2M	
Laser color:	R/G	
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm	
Light effect		

Spotlight	
LED type:	3 x 4 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	7°
Beam angle (1/2 peak):	Spot 7°
Beam angle (1/10 peak):	Spot 20°
Bar	
LED type:	4 x 1,5 W SMD 8072 ultra violet (UV)
Flash rate:	0 - 30 Hz