

EUROLITE PSL-250 showlaser RGB

High performance laser

Art. No.: 51741410

GTIN: 4026397353952



The article is no longer in our assortment.

Features:

- Laser with the classification 3B
- RGB-color-mixture
- Operation: ILDA, DMX512, auto, sound-active
- Effects: layers, grids, tunnels, waves, writing, graphics, animation
- Laser diode: 650 nm red, 532 nm green, 473 nm blue
- For DMX-operation on the rear panel: X and Y size adjustment, white balance
- Laser safety by integrated scan control, interlock with mechanic shutter, key switch for locking startup
- Read user manual before use. Laser installation, alignment and operation only by qualified and trained personell! Never open the housing!

Logistic

EAN / GTIN: 4026397353952

Weight: 41,20 kg

Length: 0.73 m

Width: 0.55 m

Heigth: 0.48 m

Bulky product

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 80,00 W

Dimensions: Width: 60 cm
Depth: 20 cm
Height: 24 cm

DMX channels: 11

DMX connection: 3-pin XLR

ILDA-connection: 25-pin SUB-D

| | |
|---|-------------------------------------|
| Maximum optical power: | 250 mW |
| Laser classification: | 3B |
| Wavelength: | 650/532/473 nm |
| Laser-modules: | Red 150 mW, green 60 mW, blue 50 mW |
| Beam: | approx. 4 mm / 1 mrad |
| Galvos: | max. ILDA 24K |
| Scanning speed: | 30000 pps |
| Dimensions without bracket (L x W x H): | 600 x 400 x 240 mm |
| Weight: | 15 kg |