LASERWORLD BeamBar 10G-532

Laser bar class 3B with 10 x 90 mW laser power in green

Art. No.: 51743231

GTIN: 7640144997229

The article is no longer in our assortment.

Description:

This special laser effect creates fans of laser beams and can be controlled through DMX or runs in stand-alone or music mode.

The BeamBar 10G-532 is a bar with 10 single beam laser outlets, each equipped with a green DPSS laser source 90 mW / 532 nm.

The advantages of the BeamBar 10G-532 are:

a very bright green
very affordable
a very good beam profile

This show laser light provides an analog modulation. It means a better color fading and a much broader color hue. These facts make the Laserworld BeamBar devices ideal for all applications requiring many different color hues and color fadings.

Each laser beam can be individually aligned through a 4-point alignment system, that can easily be accessed from the front - so opening the housing is not necessary.

The BeamBar 10G-532 can be controlled through 13 DMX channels, so each laser source can be controlled individually. Thus it is possible to create many different chaser, beam or fan effects.

Due to the standard DMX compatibility, the BeamBar 10G-532 can easily be integrated into an existing lighting setup.

This laser projector provides a master-slave-mode. Show lasers of the same series (slave projectors), connected via DMX to a main projector (master projector) project the same patterns like the master projector.

Logistic

EAN / GTIN: 7640144997229
Weight: 11,00 kg
Length: 1.10 m
Width: 0.26 m
Heigh: 0.19 m

The BeamBar 10G-532 is a great effect for stages, live gigs and nightclubs, as well as for TV Shows and show productions.

Features:

Technical specifications:

IP classification:	IP20
Laser class:	3B
Laser color:	Green (G)
Housing color:	Black
Dimensions:	Length: 1 m Depth: 16 cm Height: 8 cm
Guaranteed power at aperture:	900 mW
Power Green:	10 x 90 mW / 532 nm
Beam Specifications:	<3.0 mm / <1.5 mrad
Laser Sources:	DPSS
Laser Class:	3B
Operation Modes:	DMX, Stand-alone, Sound-to-Light, master-slave
Accessories:	Interlock connector, manual, key
Power supply:	100-250 V AC 50/60 Hz
Power Consumption:	50 W
Dimensions (L x W x H):	1000 x 160 x 80 mm
Weight:	9 kg