

LASERWORLD DS-1000RGB MK3

Diode showlaser with ShowNET network interface and free software

Art. No.: 51743281

GTIN: 7640144997502



The article is no longer in our assortment.

Features:

- Integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; ILDA; ArtNet; Master/slave function
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x laser, 1 x user manual, 1 x power cord, 1 x interlock, 2 x key, 1 x bag

Logistic

EAN / GTIN: 7640144997502

Weight: 4,60 kg

Length: 0.35 m

Width: 0.28 m

Height: 0.18 m

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 40 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Laser class: | 4 |
| Laser color: | R/G/B |
| Laser module: | Red (R) 200 mW 638nm Green (G) 250 mW 520nm Blue (B) 700 mW 450nm |

| | |
|----------------|---|
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; ILDA; ArtNet; Master/slave function |
| Housing color: | Black |
| Dimensions: | Width: 14 cm Depth: 20 cm Height: 11 cm |
| Weight: | 3,90 kg |