

EUROLITE LED TMH-46 Moving Head Wash

Compact moving washlight with 6in1 LEDs

Art. No.: 51785892 GTIN: 4026397625141











List price: 177.31 €

incl. 19% VAT.

Features:

- 4 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Positioning within 540° PAN, 220° TILT
- Exact positioning (16 bit resolution)
- Motion macros adjustable; Dimmer electronic; color blend stepless; color macros adjustable
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone; master/slave function
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Flicker-free
- With a beam angle of 24°
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 2 x screw, 4 x washer

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397625141

Weight: 2,02 kg Length: 0.20 m Width: 0.17 m Heigth: 0.26 m

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	4 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Max. TILT movement:	220° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	1,5 - 22 Hz
DMX channels:	16; 18
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; master/slave function
Preprogrammed in:	Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	24°
Beam angle : Beam angle (1/2 peak):	24° 24°
Beam angle (1/2 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx
Beam angle (1/2 peak): Beam angle (1/10 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx
Beam angle (1/2 peak): Beam angle (1/10 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx
Beam angle (1/2 peak): Beam angle (1/10 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx
Beam angle (1/2 peak): Beam angle (1/10 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx
Beam angle (1/2 peak): Beam angle (1/10 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx
Beam angle (1/2 peak): Beam angle (1/10 peak):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx):	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx): Housing color:	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx Black
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx): Housing color: Display type:	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx Black 4 digit 7-segment LED display
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx): Housing color: Display type:	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx Black 4 digit 7-segment LED display Width: 14,5 cm
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx): Housing color: Display type:	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx Black 4 digit 7-segment LED display Width: 14,5 cm Depth: 14 cm
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx): Housing color: Display type: Dimensions:	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx Black 4 digit 7-segment LED display Width: 14,5 cm Depth: 14 cm Height: 18 cm
Beam angle (1/2 peak): Beam angle (1/10 peak): Illuminance in Lux (lx): Housing color: Display type: Dimensions:	24° 42° Red (R) 3m: 59 lx, 6m: 16 lx Green (G) 3m: 145 lx, 6m: 41 lx Blue (B) 3m: 29 lx, 6m: 8 lx Cold white (CW) 3m: 136 lx, 6m: 37 lx Amber (A) 3m: 47 lx, 6m: 13 lx Ultra violet (UV) 3m: 1 lx, 6m: 1 lx All 3m: 376 lx, 6m: 103 lx Black 4 digit 7-segment LED display Width: 14,5 cm Depth: 14 cm Height: 18 cm