

## EUROLITE LED TMH-X4 Moving Head Wash Zoom wh

Washlight with 19 intense 15 W 4in1 LEDs, motorized zoom and white housing

Art. No.: 51785916

GTIN: 4026397713206



### Features:

- 19 LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)<BR>3 segments controlled separately
- Positioning within 630° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by temperature-controlled fan at the head; cooling fan at the base
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; GDTF (GrandMA3)
- Flicker-free
- With a beam angle of 1° - 40°
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental; restaurants, bars and hotels
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397713206

Weight: 9,40 kg

Length: 0.45 m

Width: 0.27 m

Heigh: 0.40 m

## Technical specifications:

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power consumption:       | 225 W                                                                                                                                                                                                                                                                                                                                                                                                                              |
| IP classification:       | IP20                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                                                                                                                                                                                                                                                                                               |
| Power output:            | P-Con (gray), mounting version                                                                                                                                                                                                                                                                                                                                                                                                     |
| Fuse:                    | 5 x 20 mm, T 2 A fuse replaceable                                                                                                                                                                                                                                                                                                                                                                                                  |
| Lamp type:               | LED lamp                                                                                                                                                                                                                                                                                                                                                                                                                           |
| LED type:                | 19 x 15 W COB (chip-on-board) 4in1 QCL RGBW<br>(homogenous color mix)                                                                                                                                                                                                                                                                                                                                                              |
| Max. TILT movement:      | 270° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                                                                                                                                                                                                                                                                                                                  |
| Max. PAN movement:       | 630° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                                                                                                                                                                                                                                                                                                                  |
| Equipment:               | Zoom motor driven                                                                                                                                                                                                                                                                                                                                                                                                                  |
| DMX channels:            | 16; 24                                                                                                                                                                                                                                                                                                                                                                                                                             |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                                                                                                                                                                                                                                                                     |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                                                                                                                                                                                                                                                                     |
| Cooling:                 | Temperature-controlled fan at the head<br>Cooling fan at the base                                                                                                                                                                                                                                                                                                                                                                  |
| Control:                 | Stand-alone; DMX; sound to light via microphone;<br>master/slave function; QuickDMX via USB<br>(optional); W-DMX by wireless solution via USB<br>(optional); CRMX by LumenRadio via USB<br>(optional)                                                                                                                                                                                                                              |
| Fixtures available for:  | Light´J; LED PC-Control 512; EASY SHOW 1;<br>Light Captain; GDTF (GrandMA3)                                                                                                                                                                                                                                                                                                                                                        |
| Projection:              | Flicker-free                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Beam angle:              | 1° - 40°                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Beam angle (1/2 peak):   | 1 - 25°                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Beam angle (1/10 peak):  | 8 - 40°                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 2779 lx, 6m: 763 lx<br>Narrow green (G) 3m: 7893 lx, 6m: 1841 lx<br>Narrow blue (B) 3m: 1468 lx, 6m: 390 lx<br>Narrow cold white (CW) 3m: 9558 lx, 6m: 2468 lx<br>Narrow all 3m: 19553 lx, 6m: 5001 lx<br>Wide red (R) 3m: 272 lx, 6m: 73 lx<br>Wide green (G) 3m: 583 lx, 6m: 160 lx<br>Wide blue (B) 3m: 117 lx, 6m: 34 lx<br>Wide cold white (CW) 3m: 740 lx, 6m: 211 lx<br>Wide all 3m: 1568 lx, 6m: 439 lx |
| Housing color:           | White                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Display type:            | Multicolor LCD display                                                                                                                                                                                                                                                                                                                                                                                                             |
| Dimensions:              | Width: 30.5 cm<br>Depth: 20.0 cm<br>Height: 40.0 cm                                                                                                                                                                                                                                                                                                                                                                                |
| Weight:                  | 8.62 kg                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                       |                                              |
|-----------------------|----------------------------------------------|
| Noise classification: | Class 3 (clearly perceptible sounds)         |
| Special product:      | Not designed for household room illumination |
| Intended use:         | Show effect lighting                         |

### **Scope of delivery:**

---

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket