

EUROLITE LED TMH-H240 Beam/Wash/Flower Effect

Hybrid moving head with RGBW LEDs, zoom, macros, patterns and color temperature presets

Art. No.: 51785925

GTIN: 4026397710779



List price: 831.81 €

incl. 19% VAT.

Features:

- 3in1 moving head beam, wash and flower effect in one device
- 6 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Positioning within 540° PAN and 240° TILT
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor-driven; lens rotation
- Color blend stepless; color change; colors preset; patterns preset; background color adjustable; Dimmer speed (step response) adjustable
- Strobe effect; fan effect; flower effect; multi beam effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); WDMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Master/slave function
- Flicker-free
- With a beam angle of 2° - 40°
- With Omega bracket
- LCD display
- Preprogrammed in Light Captain; EASY SHOW 3; Light´J
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer; Stage
- Application possibility: Standing; suspended

Package contents

Logistic

EAN / GTIN: 4026397710779

Weight: 6,60 kg

Length: 0.31 m

Width: 0.23 m

Height: 0.42 m

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 1 x xLR cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	190 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3 A
Lamp type:	LED lamp
LED:	6 x 40 W 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	240° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540°, 360° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	1 - 25 Hz
Equipment:	Zoom motor-driven; lens rotation
DMX channels:	16; 21; 24; 32; 56
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Master/slave function
Preprogrammed in:	Light Captain; EASY SHOW 3; Light´J
Projection:	Flicker-free
Beam angle:	2° - 40°
Beam angle (1/2 peak):	2 - 25°
Beam angle (1/10 peak):	8 - 40°
Illuminance in Lux (lx):	Narrow red (R) 1m: 11423 lx, 3m: 5703 lx, 6m: 1423 lx Narrow green (G) 1m: 28573 lx, 3m: 11882 lx, 6m: 2992 lx Narrow blue (B) 1m: 3089 lx, 3m: 1835 lx, 6m: 513 lx Narrow cold white (CW) 1m: 35392 lx, 3m: 15489 lx, 6m: 3899 lx Narrow all 1m: 67721 lx, 3m: 30843 lx, 6m: 7807 lx
Housing color:	Black
Attachment system:	2x Omega bracket
Display type:	LCD display
Dimensions:	Width: 26 cm Depth: 18 cm

Height: 33 cm

Weight: 6,10 kg

Noise classification: Class 3 (clearly perceptible sounds)

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting
