

EUROLITE LED TMH-W480 Moving Head Wash Zoom

Washlight with 12 bright 40 W RGBW LEDs, zoom, pixel control, pattern effects

Art. No.: 51785935

GTIN: 4026397713626



Features:

- 12 LEDs 40 W 4in1 QCL RGBW (homogenous color mix)
12 LEDs controlled separately
- Positioning within 540° PAN, 215° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer
- Zoom motor driven; Dimmer
- Color blend stepless; color change adjustable; color animations with two adjustable colors
- Strobe effect
- Integrated show programs
- Direct color selection
- The device is cooled by temperature-controlled fan at the head; low-noise cooling fan at the base
- Control via stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone; master/slave function
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 1° - 35°
- Multicolor LCD display
- Mains input and output for power linking up to 4 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; theater; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397713626

Weight: 16,00 kg

Length: 0.47 m

Width: 0.36 m

Height: 0.47 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	475 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	12 x 40 W 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	215° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0.5 - 11 Hz
Equipment:	Zoom motor driven; Dimmer
DMX channels:	11; 16; 18; 58
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the head Low-noise cooling fan at the base
Control:	Stand-alone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	16000 Hz
Beam angle:	1° - 35°
Beam angle (1/2 peak):	1 - 18°
Beam angle (1/10 peak):	6 - 35°
Illuminance in Lux (lx):	Narrow red (R) 1m: 10753 lx, 3m: 4966 lx, 6m: 1572 lx Narrow green (G) 1m: 30231 lx, 3m: 12941 lx, 6m: 4189 lx Narrow blue (B) 1m: 3586 lx, 3m: 2214 lx, 6m: 830 lx Narrow cold white (CW) 1m: 29150 lx, 3m: 12657 lx, 6m: 4024 lx Narrow all 1m: 66539 lx, 3m: 31156 lx, 6m: 10125 lx Wide red (R) 1m: 2592 lx, 3m: 363 lx, 6m: 99 lx Wide green (G) 1m: 7263 lx, 3m: 966 lx, 6m: 265 lx Wide blue (B) 1m: 1368 lx, 3m: 188 lx, 6m: 51 lx

Wide cold white (CW) 1m: 6610 lx, 3m: 887 lx,
6m: 242 lx

Wide all 1m: 16995 lx, 3m: 2285 lx, 6m: 622 lx

Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 39.0 cm Depth: 27.0 cm Height: 47.0 cm
Weight:	14.65 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x device
1 x user manual
1 x power cord
2 x omega bracket