

EUROLITE LED TMH-21.i Twin Moving Head Beam

RGBW Mini-Beam with 2 controllable heads and unlimited PAN movement

Art. No.: 51785979

GTIN: 4026397551525



The article is no longer in our assortment.

Features:

- With Infinity function for unlimited PAN movement
- TILT movement for each LED head separately and steplessly adjustable
- Equipped with two 10 W quadcolor LEDs (CREE) with RGBW colors
- Each LED can be controlled individually
- Narrow beam angle
- Compact lightweight
- 17 or 24 DMX channels selectable
- Functions: Colored beams in R, G, B and W, auto mode, sound control, color presets, strobe settings, Master/Slave function, built-in programs
- Stepless RGBW color mixture
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Addressing via control panel with 4-digit LED display
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 2 powerful LEDs 10 W high-power 4in1 QCL RGBW
- Exact positioning (16 bit resolution)
- Multi beam effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light Captain; Light 'J
- Flicker-free

Logistic

EAN / GTIN: 4026397551525

Weight: 3,33 kg

Length: 0.25 m

Width: 0.18 m

Height: 0.28 m

- With a beam angle of 5°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	2 x 10 W high-power 4in1 QCL RGBW
Max. TILT movement:	270° Exact positioning (16 bit resolution)
Max. PAN movement:	Exact positioning (16 bit resolution) plus infinity
Flash rate:	0 - 18 Hz
DMX channels:	17; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	5°
Beam angle (1/2 peak):	5°
Illuminance in Lux (lx):	Red (R) 3m: 540 lx, 6m: 177 lx Green (G) 3m: 1097 lx, 6m: 305 lx Blue (B) 3m: 222 lx, 6m: 60 lx Cold white (CW) 3m: 1686 lx, 6m: 454 lx
Housing color:	Black
Dimensions:	Width: 21,5 cm Depth: 12,5 cm Height: 23 cm
Weight:	2,85 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting