

## EUROLITE LED TMH-X1 Moving Head Beam

60 W beam, compact, narrow angle, beautiful RGBW colors

Art. No.: 51785988

GTIN: 4026397573633



**List price: 474.81 €**

incl. 19% VAT.

### Features:

- Compact lightweight
  - 1 powerful LED 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
  - Positioning within 540° PAN and 220° TILT
  - Auto position correction (feedback)
  - Exact positioning (16 bit resolution)
  - Color selection; color blend stepless; Dimmer electronic
  - Beam effect; Strobe effect
  - Integrated show programs
  - The device is cooled by cooling fan
  - Control via DMX; stand-alone; Sound to light via Microphone
  - Flicker-free
  - With a beam angle of 3°
  - OSRAM bulb included
  - Preprogrammed in Light J; LED PC-Control 512; Light Captain
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer
  - Application possibility: Standing; suspended
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x xLR cable

### Logistic

EAN / GTIN: 4026397573633

Weight: 5,00 kg

Length: 0.29 m

Width: 0.29 m

Height: 0.33 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 60 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	0 - 10 Hz
DMX channels:	14
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; Sound to light via Microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	3°
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	7°
Illuminance in Lux (lx):	Red (R) 3m: 3251 lx, 6m: 712 lx Green (G) 3m: 4684 lx, 6m: 1125 lx Blue (B) 3m: 819 lx, 6m: 220 lx Cold white (CW) 3m: 7909 lx, 6m: 1899 lx All 3m: 15489 lx, 6m: 3655 lx
Housing color:	Black
Use of brands:	OSRAM bulb included
Dimensions:	Width: 20,7 cm Depth: 19,6 cm Height: 31,3 cm
Weight:	4,29 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting