

EUROLITE LED TMH-X12 Moving-Head Spot

Bright spot with 120 W LED, rotating gobos, color wheel and prism

Art. No.: 51785992 GTIN: 4026397553147











List price: 891.31 €

incl. 19% VAT.

Features:

- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; Prism 3-fold; Focus motor-driven
- Multi beam effect; gobo effect; Strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone
- Flicker-free
- With a beam angle of 12°
- LCD display
- Dimmer electronic
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; Rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Logistic

EAN / GTIN: 4026397553147

Weight: 13,05 kg Length: 0.54 m Width: 0.43 m Heigth: 0.31 m

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|-------------------------------|--|
| Power consumption: | 170 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 1 x 120 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 270° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Max. PAN movement: | 540° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Flash rate: | 0 - 18 Hz |
| Equipment: | Gobo wheel with rotating gobos; Prism 3-fold; Focus motor-driven |
| Color generation: | Color wheel with 8 dichroic filters plus open |
| | Half colors selectable, Rainbow effect with adjustable speed |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open |
| | Outside diameter 23,5mm |
| | Image diameter 15mm |
| | Shake effect |
| | Gobos changeable Slot-in gobo system for easy gobo replacement |
| DMX channels: | 13; 15 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; Sound to light via Microphone |
| Preprogrammed in: | Light 'J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 12° |
| Beam angle (1/2 peak): | 12° |
| Illuminance in Lux (lx): | Cold white (CW) 3m: 9502 lx, 6m: 2436 lx |
| Housing color: | Black |
| Display type: | LCD display |
| Dimensions: | Width: 33 cm |
| | Depth: 32 cm |
| | Height: 40 cm |
| | |
| Weight: | 11,35 kg |
| Weight: Noise classification: | 11,35 kg Class 3 (clearly perceptible sounds) |

| Special product: | Not designed for household room illumination |
|------------------|--|
| Intended use: | Show effect lighting |