

EUROLITE LED TMH Bar S120 Moving Head Spots

LED lighting system with 4 individually controllable 30 W moving heads

Art. No.: 51786055

GTIN: 4026397728958



Features:

- Crossbar with integrated DMX control unit and stand sleeve
- 4 LEDs 30 W COB (chip-on-board)
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual; color wheel
- Dimmer electronic
- Strobe effect; beam effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with static gobos, 7 gobos and open
shake effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for Colorchief; Light J; Light Captain
- Flicker-free
- With a beam angle of 13°
- With omega bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397728958

Weight: 15,00 kg

Length: 1.08 m

Width: 0.34 m

Height: 0.26 m

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 100 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 4 x 30 W COB (chip-on-board) |
| Max. TILT movement: | 180° positioning; exact positioning (16 bit resolution) |
| Max. PAN movement: | 540° positioning; exact positioning (16 bit resolution) |
| Flash rate: | 2 - 14 Hz |
| Equipment: | Gobo wheel with static gobos; focus manual; color wheel |
| Color generation: | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed |
| Gobos: | Gobo wheel with static gobos, 7 gobos and open Shake effect |
| DMX channels: | 3; 5; 9; 11; 17; 21; 30; 38 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Fixtures available for: | Colorchief; Light J; Light Captain |
| Projection: | Flicker-free |
| PWM frequency: | 11000 Hz |
| Beam angle: | 13° |
| Beam angle (1/2 peak): | 13° |
| Color temperature: | 7300K |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 8899 lx, 3m: 856 lx, 6m: 205 lx |
| Housing color: | Black |
| Attachment system: | 2x omega bracket Tube: Ø 35mm |
| Display type: | 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 100.0 cm |

Depth: 17.5 cm
Height: 28.0 cm

| | |
|-----------------------|--|
| Weight: | 13.00 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket
2 x safety eyelet