

EUROLITE LED TMH-S60 Moving Head Spot wh

Compact Moving moving head with 60 W LED, gobos, color wheel and white housing

Art. No.: 51786073

GTIN: 4026397713213



Features:

- 3 gobos with heart patterns for exchange included
- 1 LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 180° TILT
- Gobo wheel with rotating gobos; focus manual; color wheel
- Dimmer electronic
- Beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
slot-in gobo system for easy gobo replacement
- Shake effect
- 4 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; Light 'J
- Flicker-free
- With a beam angle of 12°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397713213

Weight: 3,55 kg

Length: 0.29 m

Width: 0.21 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 1.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	180° positioning
Max. PAN movement:	540° positioning
Flash rate:	1.5 - 23 Hz
Equipment:	Gobo wheel with rotating gobos; focus manual; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 13.8mm Image diameter 11mm Slot-in gobo system for easy gobo replacement Shake effect
DMX channels:	10; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; Light J
Projection:	Flicker-free
PWM frequency:	2700 Hz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Color temperature:	7700K
Illuminance in Lux (lx):	Cold white (CW) 1m: 15205 lx, 3m: 1764 lx, 6m: 445 lx
Housing color:	White
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 17.0 cm Depth: 15.0 cm Height: 24.0 cm

Weight:	3.15 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x safety eyelet
- 3 x gobos