

## EUROLITE LED TMH-S200 Moving Head Spot

LED moving head spot with color wheel, static & rot. gobo wheel, prism, frost, focus and zoom

Art. No.: 51786088

GTIN: 4026397677836



### Features:

- 1 LED 200 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
- Dimmer electronic; Dimmer speed (step response) adjustable
- Color wheel with 9 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 9 gobos and open<BR>shake effect
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Slot-in gobo system for easy gobo replacement
- Gobos changeable
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRM by LumenRadio via USB (optional)
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 8° - 22°
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397677836

Weight: 16,30 kg

Length: 0.51 m

Width: 0.42 m

Height: 0.42 m

## Technical specifications:

|                          |                                                                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                                       |
| Power consumption:       | 250 W                                                                                                                                                                                                                                                        |
| IP classification:       | IP20                                                                                                                                                                                                                                                         |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                                                                              |
| Power output:            | P-Con (gray), mounting version                                                                                                                                                                                                                               |
| Device fuse:             | 5 x 20 mm, T 3.15 A fuse replaceable                                                                                                                                                                                                                         |
| Lamp type:               | LED lamp                                                                                                                                                                                                                                                     |
| LED type:                | 1 x 200 W COB (chip-on-board) cold white (CW)                                                                                                                                                                                                                |
| Max. TILT movement:      | 270° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                                                                                                                                            |
| Max. PAN movement:       | 540° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                                                                                                                                            |
| Flash rate:              | 1 - 18 Hz                                                                                                                                                                                                                                                    |
| Equipment:               | Prism 3-fold rotating; frost filter; gobo wheel with<br>rotating gobos; gobo wheel with static gobos;<br>zoom motor driven; focus motor-driven; color<br>wheel                                                                                               |
| Color generation:        | Color wheel with 9 dichroic filters plus open<br>Half colors selectable, Rainbow effect with<br>adjustable speed in both directions                                                                                                                          |
| Gobos:                   | Gobo wheel with static gobos, 9 gobos and open<br>Shake effect<br>Gobo wheel with rotating gobos, 7 gobos and<br>open<br>Outside diameter 19.5mm<br>Image diameter 15mm<br>Shake effect<br>Slot-in gobo system for easy gobo replacement<br>Gobos changeable |
| DMX channels:            | 17                                                                                                                                                                                                                                                           |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                                                                                               |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                                                                                               |
| Cooling:                 | Cooling fan                                                                                                                                                                                                                                                  |
| Control:                 | Stand-alone; DMX; master/slave function; sound<br>to light via microphone; QuickDMX via USB<br>(optional); W-DMX by wireless solution via USB<br>(optional); CRMX by LumenRadio via USB<br>(optional)                                                        |
| Fixtures available for:  | Light Captain                                                                                                                                                                                                                                                |
| Projection:              | Flicker-free                                                                                                                                                                                                                                                 |
| Beam angle:              | 8° - 22°                                                                                                                                                                                                                                                     |
| Beam angle (1/2 peak):   | 8 - 22°                                                                                                                                                                                                                                                      |
| Beam angle (1/10 peak):  | 8 - 22°                                                                                                                                                                                                                                                      |
| Illuminance in Lux (lx): | Narrow cold white (CW) 3m: 22622 lx, 6m: 6278<br>lx<br>Wide cold white (CW) 1m: 31619 lx, 3m: 4309 lx,<br>6m: 1112 lx                                                                                                                                        |

|                       |                                                     |
|-----------------------|-----------------------------------------------------|
| Housing color:        | Black                                               |
| Display type:         | Multicolor LCD display                              |
| Dimensions:           | Width: 30.5 cm<br>Depth: 33.0 cm<br>Height: 51.5 cm |
| Weight:               | 14.70 kg                                            |
| Noise classification: | Class 3 (clearly perceptible sounds)                |
| Special product:      | Not designed for household room illumination        |
| Intended use:         | Show effect lighting                                |

**Scope of delivery:**

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket