

EUROLITE LED TMH-75 Hybrid Moving-Head Spot/Wash COB wh

Bright spotlight and full-fledged washlight with 75 W LED

Art. No.: 51786090

GTIN: 4026397665918



The article is no longer in our assortment.

Features:

- Equipped with a white 75 W COB LED and nine 8 W 6in1LEDs in the colors red, green, blue, amber, white and UV
- Compact lightweight
- 7 brilliant, dichroic colors plus white
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 6 rotating gobos plus open
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer (0-100%)
- Motorized focus
- Programmable color-change speed and strobe effect
- Stepless color blend
- Color macros can be called up via DMX controller
- Exact positioning via 16-bit PAN/TILT movement resolution
- PAN angle switchable between 540°, 360° and 180°
- TILT angle switchable between 270°, 180° and 90°
- Stand-alone, master/slave and DMX mode
- Control panel with LC display for easy configuration
- 9 powerful LEDs 8 W 6in1 HCL RGBWA/UV (homogenous color mix)
- 1 powerful LED 75 W COB (chip-on-board) color wheel (homogenous color mix)
- TILT angle switchable between 270° and 180°
- PAN angle switchable between 540° and 360°; and 180°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
- Color wheel with 7 dichroic filters plus open

Logistic

EAN / GTIN: 4026397665918

Weight: 9,55 kg

Length: 0.42 m

Width: 0.36 m

Height: 0.37 m

- Gobo wheel with rotating gobos, 6 gobos and open
 - The device is cooled by cooling fan
 - Control via stand-alone; sound to light via microphone; DMX
 - Preprogrammed in EASY SHOW 1; Light Captain; Light´J
 - With a beam angle of 12°
 - LCD display
- Package contents**
- 1 x moving light, 2 x omega bracket, 4 x screw, 1 x user manual, 1 x power cord, 1 x XLR cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 8 W 6in1 HCL RGBWA/UV (homogenous color mix) 1 x 75 W COB (chip-on-board) color wheel (homogenous color mix)
Max. TILT movement:	270°, 180° exact positioning (16 bit resolution) auto position correction (feedback); 90° positioning
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback); , 180°
Equipment:	Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 6 gobos and open
DMX channels:	21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; sound to light via microphone; DMX
Preprogrammed in:	EASY SHOW 1; Light Captain; Light´J
Beam angle:	12°
Beam angle (1/2 peak):	Spot 12° Wash effect 28°
Illuminance in Lux (lx):	Wash effect red (R) 3m: 24 lx, 6m: 7 lx Wash effect green (G) 3m: 133 lx, 6m: 36 lx Wash effect blue (B) 3m: 20 lx, 6m: 6 lx Wash effect cold white (CW) 3m: 92 lx, 6m: 26 lx Wash effect amber (A) 3m: 31 lx, 6m: 9 lx Wash effect ultra violet (UV) 3m: 1 lx, 6m: 1 lx Wash effect all 3m: 288 lx, 6m: 78 lx Spot cold white (CW) 3m: 3942 lx, 6m: 1008 lx
Housing color:	White
Display type:	LCD display
Dimensions:	Width: 25,5 cm

Depth: 25 cm
Height: 31 cm

Weight:	8,20 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting