

## EUROLITE LED TSL-350 Scan COB

Handy scanner with 60 W COB LED, gobo and color wheel

Art. No.: 51786150

GTIN: 4026397709414



### Features:

- Compact design
- 1 LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within
- Color wheel; gobo wheel with rotating gobos; focus manual
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open<BR>gobos changeable
- Slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; Light´J; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 11°
- LCD display
- Rubber feet
- Available in various colors
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397709414

Weight: 3,60 kg

Length: 0.40 m

Width: 0.22 m

Height: 0.21 m

## Technical specifications:

|                          |                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                    |
| Power consumption:       | 70 W                                                                                                                                                                                      |
| IP classification:       | IP20                                                                                                                                                                                      |
| Protection class:        | Protection class I                                                                                                                                                                        |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                          |
| Fuse:                    | 5 x 20 mm, T 1.5 A fuse replaceable                                                                                                                                                       |
| Lamp type:               | LED lamp                                                                                                                                                                                  |
| LED type:                | 1 x 60 W COB (chip-on-board) cold white (CW)                                                                                                                                              |
| Equipment:               | Color wheel; gobo wheel with rotating gobos; focus manual                                                                                                                                 |
| Color generation:        | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed                                                                                |
| Gobos:                   | Gobo wheel with rotating gobos, 7 gobos and open<br>Outside diameter 14mm<br>Image diameter 10mm<br>Gobos changeable<br>Slot-in gobo system for easy gobo replacement<br>Shake effect     |
| DMX channels:            | 10                                                                                                                                                                                        |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                            |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                            |
| Cooling:                 | Cooling fan                                                                                                                                                                               |
| Control:                 | Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:  | Light Captain; Light J; EASY SHOW 2; EASY SHOW 3                                                                                                                                          |
| Projection:              | Flicker-free                                                                                                                                                                              |
| Beam angle:              | 11°                                                                                                                                                                                       |
| Beam angle (1/2 peak):   | 11°                                                                                                                                                                                       |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 12034 lx, 3m: 1489 lx, 6m: 388 lx                                                                                                                                     |
| Housing color:           | Black                                                                                                                                                                                     |
| Display type:            | LCD display                                                                                                                                                                               |
| Transport aid:           | Rubber feet                                                                                                                                                                               |
| Dimensions:              | Width: 16.0 cm<br>Depth: 15.0 cm<br>Height: 33.0 cm                                                                                                                                       |
| Weight:                  | 3.22 kg                                                                                                                                                                                   |
| Special product:         | Not designed for household room illumination                                                                                                                                              |
| Intended use:            | Show effect lighting                                                                                                                                                                      |

## Scope of delivery:

---

1 x moving light  
1 x user manual  
1 x power cord  
1 x mounting bracket  
3 x gobos