

EUROLITE LED SL-350 DMX Search Light

Follow spot with cold white 300 W LED for medium distances

Art. No.: 51787316 GTIN: 4026397589740











List price: 1783.81 €

incl. 19% VAT.

Features:

- Manual control via control panel with buttons and faders
- 1 powerful LED 300 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- Dimmer electronic
- Strobe effect
- Color wheel with 5 dichroic filters plus open
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- With a beam angle of 10°
- Direct color temperature selection for 3 preset values
- With mounting bracket
- 4 digit 7-segment LED display
- Suitable for a range of use from to 30 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x XLR cable, 1 x mounting bracket, 1 x hex key

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 440 W |
| IP classification: | IP20 |

Logistic

EAN / GTIN: 4026397589740

Weight: 11,90 kg Length: 0.66 m Width: 0.30 m Heigth: 0.28 m

| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
|--------------------------|-------------------------------------------------------------------------------------------------|
| Fuse: | 5 x 20 mm, T 5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 300 W COB (chip-on-board) cold white (CW) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Focus manual; iris stepless |
| Color generation: | Color wheel with 5 dichroic filters plus open |
| DMX channels: | 6 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX |
| Preprogrammed in: | Light´J; LED PC-Control 512; Light Captain |
| Beam angle: | 10° |
| Beam angle (1/2 peak): | 10° |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Material: | Aluminum casting; metal |
| Range of use: | - 30m |
| Dimensions: | Length: 60 cm |
| | Width: 27,5 cm Height: 30 cm |
| Weight: | 10,55 kg |
| Noise classification: | Class 2 (slight noise) |
| Power cord | Class 2 (siigiit Hoise) |
| Cable construction: | 3 x 1,5 mm² H05VV-F |
| Cable length: | Approx. 1,4 m |
| XLR cable | лургол. 1,4 ш |
| Cable length: | Approx. 2 m |
| Mounting bracket | , , , , , , , , , , , , , , , , , , , |
| Diameter mounting holes: | 3 x Ø13mm; 2 x Ø15mm |
| Material: | Metal, 4 mm |
| Hex key | |
| Dimensions: | Width: 6 cm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |