

EUROLITE LED SL-600 DMX Search Light

Follow spot with cold white 600 W LED for long distances, zoom, DMX

Art. No.: 51787330

GTIN: 4026397625066



List price: 3568.81 €

incl. 19% VAT.

Features:

- Manual control via movable control panel with buttons and faders
- 1 powerful LED 600 W COB (chip-on-board) cold white (CW)
- Focus manual; Iris stepless
- The device is cooled by cooling fan
- Control via DMX
- With a beam angle of 7° - 13°
- With Mounting bracket
- LCD display
- Direct color temperature selection for 3 preset values
- Dimmer electronic
- Strobe effect
- Suitable for a range of use from 50 to 100 meters
- Color wheel with 7 dichroic filters plus open half colors selectable
- Preprogrammed in LED PC-Control 512; Light Captain
- Built with SEETRONIC connector
- For application areas such as: Wedding/gala/events; Stage; theater; Rental
- Application possibility: On stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397625066

Weight: 22,50 kg

Length: 1.19 m

Width: 0.38 m

Height: 0.40 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 640 W

| | |
|-------------------------|---|
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED: | 1 x 600 W COB (chip-on-board) cold white (CW) |
| Color temperature: | 6500K |
| Flash rate: | 1 - 20 Hz |
| Equipment: | Focus manual; Iris stepless |
| Color generation: | Color wheel with 7 dichroic filters plus open Half colors selectable |
| DMX channels: | 5 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX |
| Preprogrammed in: | LED PC-Control 512; Light Captain |
| Beam angle: | 7° - 13° |
| Beam angle (1/2 peak): | 7 - 13° |
| Beam angle (1/10 peak): | 7 - 13° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Use of brands: | Built with SEETRONIC connector |
| Range of use: | 50m - 100m |
| Dimensions: | Length: 1,05 m Width: 23 cm Height: 34 cm |
| Weight: | 18,50 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |