

## EUROLITE LED LP-100 Logo Projector MK2

Professional gobo projector with additional color wheel

Art. No.: 51799326

GTIN: 4026397745337



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
  - Gobos rotating; zoom manual; focus manual
  - Dimmer electronic; color selection direct; Rotation speed adjustable; Rotation direction adjustable; program selection manual
  - Gobo effect; spot effect
  - Color wheel with 5 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
  - Gobo wheel with rotating gobos<BR>gobos changeable
  - Gobo indexable
  - 3 integrated show programs
  - The device is cooled by temperature-controlled fan
  - Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
  - Preprogrammed in Light Captain
  - Flicker-free
  - DMX fail mode (hold; blackout)
  - With a beam angle of 12° - 25°
  - Monochrome 4 digit 7-segment LED display
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels
  - Application possibility: Standing; suspended; on stand
- mounting bracket**
- With double bracket

### Package contents

### Logistic

EAN / GTIN: 4026397745337

Weight: 5,24 kg

Length: 0.42 m

Width: 0.21 m

Height: 0.20 m

- 1 x device, 1 x user manual, 1 x power cord, 1 x gobo holder, 3 x gobos, 2 x mounting bracket, 2 x knurled screw, 4 x washer

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 230V AC 1000 mA
Power consumption:	100 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 3 A fuse replaceable
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Flash rate:	0,4 - 24 Hz
Equipment:	Gobos rotating; zoom manual; focus manual
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos Outside diameter 32,6mm Image diameter 21mm Gobos changeable Gobo indexable
DMX channels:	5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version Bypass
Cooling:	2 x temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
PWM frequency:	24000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	12° - 25°
Beam angle (1/2 peak):	Spot 12 - 14°
Beam angle (1/10 peak):	Spot 12 - 25°
Illuminance in Lux (lx):	Narrow cold white (CW) 1m: 133020 lx, 3m: 14449 lx, 6m: 3622 lx  Wide cold white (CW) 1m: 43370 lx, 3m: 4970 lx, 6m: 1328 lx
Housing color:	Black matte
Display type:	1 x monochrome 4 digit 7-segment LED display
USB port:	1 x type A
Material:	Metal, painted
Dimensions:	Length: 31 cm

	Width: 20 cm Height: 29 cm
Weight:	4,67 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F
Mounting bracket	
Attachment system:	Ø 12mm Double bracket
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting