

FUTURELIGHT WDS-CRMX TX IP Wireless DMX Transceiver Outdoor

Weather-proof wireless DMX transceiver, IP65

Art. No.: 51834031

GTIN: 4026397721942



Features:

- Transceiver, to be used as transmitter or receiver
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Multicolored LED indicator
- Lockable power input (IP T-Con)
- Control via W-DMX by wireless solution; CRMX by LumenRadio
- Operating range up to 600m with line-of-sight
- 2.4 GHz license-free worldwide
- Up to 10 transmitters can be operated in parallel without interference
- With omega bracket
- OLED display
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397721942

Weight: 1,55 kg

Length: 0.30 m

Width: 0.20 m

Heigh: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1.6 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug

DMX channels:	Input 512 Output 512
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	W-DMX by wireless solution; CRMX by LumenRadio
Range:	Range up to 600m with line-of-sight
Frequency band:	2.4 GHz
Parallel mode:	Max. 10 transmitter
Antenna gain:	5 dBi
Modulation:	GFSK
Attachment system:	Omega bracket
Display type:	OLED display
Status LED:	DMX, level meter
Color:	Black
Dimensions:	Length: 17.3 cm Width: 15.6 cm Height: 9.2 cm
Weight:	1.30 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x declaration of conformity