

## FUTURELIGHT PHS-575 PRO-Head Spot

Multifunctional Moving Head

Art. No.: 51838275

GTIN: 4026397267983



**The article is no longer in our assortment.**

### Description:

A real plodder!

Due to its exceedingly generous equipment, this spot is ideally suited for stages or discotheques and is definitely not going to disappoint anybody. Assembled with two color wheels, the powerful PHS-575 impresses - among other things - with its two color change modes, its gobos or because of its stepless zoom. The latter guarantees an easier installation as it is responsible for the spot's adaptability - thus the spot is very flexible and does not need to be remounted with every new incident. Relaxing!

### Features:

- Color-wheel 1 with 8 different, dichroic color filters and white
- Color-wheel 2 with 5 different, dichroic color filters and white and additionally with correction-filters 3200 K and 5,600 K and UV-filter
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Slot-in system for exchanging gobos and color filters without tools
- Gobo-wheel 1 with 6 rotating gobos plus open
- All gobos can be interchanged
- Gobo-wheel 2 with 7 static metal gobos plus open
- With gobo-shake function
- Preprogrammed prism-gobo-macros
- 3-facet prism
- Stepless frost-filter for fading the projections in or out
- Motorized focus
- Mechanic dimmer
- Steplessly adjustable iris

### Logistic

EAN / GTIN: 4026397267983

Weight: 41,00 kg

Length: 0.72 m

Width: 0.47 m

Height: 0.56 m

Bulky product

- Colored LCD-display
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Lightbeam with 15°-30° radiation angle
- Exact positioning via 16 bit Pan/Tilt movement resolution
- PAN-angle switchable between 630° and 540°
- Control board with LCD-display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- For MSR GOLD 575 SA/2 DE lamp
- DMX control via every standard DMX controller

## Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	990,00 W
DMX channels:	18
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	13 Hz
Color-wheel 1:	8 dichroic + white
Color-wheel 2:	5 dichroic, 2 correction filters, UV-filter + white
Static gobo-wheel:	7 gobos and open
Rotating gobo-wheel:	6 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	23 mm
Maximum PAN-movement 630°:	in 3.5 s
Maximum TILT-movement 265°:	in 2.5 s
Length of base (including handles):	475 mm
Width of yoke:	355 mm
Height (head horizontal):	520 mm
Weight:	35 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting