

FUTURELIGHT IP PLB-420 Moving Head beam

Weather-proof beam moving-head (IP65) with 420 W discharge lamp & CRMX wireless receiver

Art. No.: 51838830

GTIN: 4026397704969



List price: on demand €

incl. 19% VAT.

Features:

- Light source: USHIO NSL 420S discharge lamp (2000 hrs)
- Lamp installed and adjusted ex factory
- Positioning within 540° PAN and 265° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism honeycomb rotating; Prism 8-fold rotating; Focus motor-driven; gobo wheel with static gobos; color wheel
- Color wheel with 13 dichroic filters plus open-half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 14 gobos und open-shake effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; Master/slave function; DMX; RDM; CRMX by LumenRadio; ArtNet; sACN; Sound to light via Microphone
- With a beam angle of 1°
- With bracket with hinged hooks
- Multicolor LCD display, with battery buffering for easy controlling
- Suitable for outdoor use
- Scenes user-definable; pulse effect adjustable
- Strobe effect
- Preprogrammed in Light Captain
- For application areas such as: Stage; Rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x xLR cable, 1 x power cord, 2 x holder

Logistic

EAN / GTIN: 4026397704969

Weight: 45,05 kg

Length: 0.86 m

Width: 0.56 m

Height: 0.47 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	420 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A
Lamp type:	Discharge lamp
Max. TILT movement:	265° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Equipment:	Prism honeycomb rotating; Prism 8-fold rotating; Focus motor-driven; gobo wheel with static gobos; color wheel
Color generation:	Color wheel with 13 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 14 gobos und open Shake effect
DMX channels:	18
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Stand-alone; Master/slave function; DMX; RDM; CRMX by LumenRadio; ArtNet; sACN; Sound to light via Microphone
Preprogrammed in:	Light Captain
Carrier frequency:	2,4 GHz
Beam angle:	1°
Beam angle (1/2 peak):	1°
Housing color:	Black
Attachment system:	2x bracket with hinged hooks
Display type:	Multicolor LCD display battery buffering
Connections:	2 x RJ-45 (F) mounting version
Dimensions:	Width: 45 cm Depth: 35 cm Height: 76 cm
Weight:	39,70 kg
Noise classification:	Class 4 (loud noises)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting