

FUTURELIGHT Color Wave LED Moving Bar

Moving head with two tiltable LED bars and colorful beams

Art. No.: 51839005

GTIN: 4026397513141



The article is no longer in our assortment.

Features:

- TILT movement for each LED bar separately and steplessly adjustable
- Individual control of each LED
- Built-in programs
- Color presets
- Shutter sequences
- Electronic dimmer (0-100%)
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 630°
- Random strobe effect
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- 6 powerful LEDs 10 W high-power 4in1 QCL RGBW
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 2,5°

Logistic

EAN / GTIN: 4026397513141

Weight: 12,10 kg

Length: 0.54 m

Width: 0.40 m

Height: 0.34 m

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 120 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 6 x 10 W high-power 4in1 QCL RGBW |
| Max. TILT movement: | 240° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 18; 17 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; stand-alone; sound to light via microphone |
| Preprogrammed in: | LED PC-Control 512 |
| Beam angle: | 2,5° |
| Beam angle (1/2 peak): | 2,5° |
| Illuminance in Lux (lx): | Red (R) 3m: 1713 lx, 6m: 655 lx Green (G) 3m: 2074 lx, 6m: 868 lx Blue (B) 3m: 861 lx, 6m: 217 lx Cold white (CW) 3m: 4037 lx, 6m: 452 lx |
| Housing color: | Black |
| Dimensions: | Width: 46,8 cm Depth: 25 cm Height: 32,5 cm |
| Weight: | 10,30 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |