

FUTURELIGHT Color Mega Wave.i LED Moving Bar

4in1 moving-head with two separately tiltable LED bars and six beams with 40 W COB LEDs

Art. No.: 51839010

GTIN: 4026397545869



The article is no longer in our assortment.

Features:

- With Infinity function for unlimited PAN movement
- TILT movement for each LED bar separately and steplessly adjustable
- Equipped with six 40 W LEDs with RGBW colors
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- 17, 18, 20 or 39 DMX channels selectable
- Each LED can be controlled individually
- Narrow illumination angle
- Functions: built-in programs, shutter sequences, color presets for each LED independently controllable, countless RGBW colors, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- Random strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices

Logistic

EAN / GTIN: 4026397545869

Weight: 14,90 kg

Length: 0.61 m

Width: 0.40 m

Height: 0.33 m

- DMX control via every standard DMX controller
- 6 powerful LEDs 40 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512
- Flicker-free
- With a beam angle of 7°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	6 x 40 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	240° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) plus infinity Auto position correction (feedback)
Flash rate:	0 - 20 Hz
DMX channels:	17; 18; 20; 39
DMX input:	1 x 5-pin XLR (M) mounting version 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version 1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512
Projection:	Flicker-free
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	7°
Illuminance in Lux (lx):	Red (R) 3m: 3209 lx, 6m: 1777 lx Green (G) 1m: 0 lx, 3m: 6717 lx, 6m: 2801 lx Blue (B) 3m: 820 lx, 6m: 421 lx Cold white (CW) 3m: 6993 lx, 6m: 3347 lx All 3m: 16094 lx, 6m: 7504 lx
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 53,8 cm Height: 34,2 cm
Weight:	12,85 kg

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting
