FUTURELIGHT DJ-Head 250 Wash

DJ moving head washlight

Art. No.: 51839540

GTIN: 4026397229820

Description:

A classic!
For football it is a match versus Germany and England. For the music business it is a Beatles or a Stones song: a classic. In the lighting technology there are also classics. One of them is our DJ-Head that is equipped with numerous functions - such as the frost filter for a softer beam or the beam shape effect , for example - and that has really proved itself. Moreover, in comparison with the PHP-series, this washlight is even a bit cheaper. So why always aspiring to innovations while elderly devices manifest their class anew, again and again?

Features:

- CMY color mixing
- Motorized color wheel with additional 9 dichroic filters plus open
- Rainbow effect in both directions
- Frost-filter for softer beam
- Beam-shape effect: wide and flat beam can steplessly be rotated by 180°
- Shutter/dimmer unit allowing very smooth dimming and a strobe effect of 1-10 flash per sec.
- Pan movement range 530°
- Tilt movement range 280°
- Automatic Pan/Tilt position correction
- High luminous efficiency parabolic reflector
- Light output via fresnel lens with a diameter of 150 mm
- Radiation angle of gresnel lens manually adjustable between 8° and 22°
- High-quality stepper motors for smooth movements
- Control board with 4-digit display for adjusting the DMX starting address
- For MSD/HSD 250, MSD 250/2 lamp
- DMX control via every standard DMX controller

Logistic

EAN / GTIN: 4026397229820
Weight: 27,85 kg
Length: 0.51 m
Width: 0.48 m
Heigth: 0.55 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	700 W
Max. TILT movement:	280° positioning
Max. PAN movement:	530° positioning
Flash rate:	1 - 10 Hz
DMX channels:	13
Dimensions:	Length: 43.50 cm
Weight:	25.50 kg
DMX channels:	13
DMX connection:	3-pin XLR
Flash-rate:	10 Hz
Color-system:	CMY color-mixture
Color-wheel:	9 dichroic filters and open
Length of base (including handles):	435 mm
Width of yoke:	410 mm
Height (head horizontal):	500 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.