

FUTURELIGHT DSC-60 LED-Scan

PRO LED scanner with 60 W LED

Art. No.: 51839905

GTIN: 4026397503159



Features:

- 1 extra bright 60 W LED for best luminance
- 12 or 14 DMX channels selectable
- Color-wheel with 7 different, dichroic color filters, UV filter and white
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Slot-in gobo system for exchanging gobos without tools
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- With gobo shake function
- Effect wheel with rotating 3-facet prism and 3D prism
- Macro function for rotating gobos/rotating prism combinations
- Frost filter
- Motorized focus
- Dimmer
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 7 built-in programs can be called up via DMX controller
- 48 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually

Logistic

EAN / GTIN: 4026397503159

Weight: 10,10 kg

Length: 0.68 m

Width: 0.38 m

Height: 0.35 m

- The scenes in Program Run can be modified via the control board or via an external controller and loaded into the memory
- Software-upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- DMX control via every standard DMX controller
- 1 LED 60 W COB (chip-on-board) color wheel
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos
- Color wheel with 7 dichroic filters plus open and UV filter
- Gobo wheel with rotating gobos, 7 gobos and open gobos changeable
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone; RDM
- With a beam angle of 13°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) color wheel
Max. TILT movement:	45° exact positioning (16 bit resolution)
Max. PAN movement:	180° exact positioning (16 bit resolution)
Flash rate:	0 - 13 Hz
Equipment:	Gobo wheel with rotating gobos
Color generation:	Color wheel with 7 dichroic filters plus open and UV filter
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 27mm Image diameter 22mm Gobos changeable
DMX channels:	14; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; RDM
Beam angle (1/2 peak):	13°
Housing color:	Black
Dimensions:	Width: 30.1 cm Depth: 56.3 cm Height: 23.2 cm
Weight:	7.90 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery: