

FUTURELIGHT EYE-7 Zoom LED Moving-Head Wash

4in1 moving-head wash with zoom

Art. No.: 51841307

GTIN: 4026397480924



The article is no longer in our assortment.

Features:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- High PAN/TILT speed
- Supports RDM (Remote Device Management)
- 15, 17 or 24 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity, colors and zoom
- Master dimmer
- Motorized zoom with 18°-36° beam angle
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable

Logistic

EAN / GTIN: 4026397480924

Weight: 7,85 kg

Length: 0.41 m

Width: 0.32 m

Height: 0.27 m

- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120,00 W
Dimensions:	Width: 24,4 cm Depth: 17,9 cm Height: 35 cm
DMX channels:	15/17/24
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	18 Hz
LED number:	7
LED type:	15 W QCL
Beam angle:	18° - 36°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	244 x 179 x 350 mm
Weight:	6 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting