

FUTURELIGHT EYE-7 RGBW Zoom LED Moving Head Wash

PRO washlight, compact with RGBW color mixing and very large zoom range

Art. No.: 51841308

GTIN: 4026397545432



The article is no longer in our assortment.

Features:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- High PAN/TILT speed
- Exact positioning via 16 bit PAN/TILT movement resolution
- Master dimmer
- Motorized zoom with 2 - 41° beam angle
- Each color of the 7 RGBW LEDs can be switched individually
- Color presets
- Preset color temperatures
- Built-in programs
- Animated and static macros
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function

Logistic

EAN / GTIN: 4026397545432

Weight: 8,10 kg

Length: 0.46 m

Width: 0.32 m

Height: 0.27 m

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
 - Number of scenes can be changed individually
 - Software upload by optional accessories via DMX link
 - Power connection via Neutrik PowerCon jack and included power cable
 - Feed-through output allows to power another device
 - After every 8 device the fixtures must have a renewed connection with the power mains
 - DMX control via every standard DMX controller
 - 7 powerful LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
 - PAN angle switchable between 540° and 630°
 - Auto position correction (feedback)
 - Exact positioning (16 bit resolution)
 - Zoom motor driven
 - Beam effect
 - The device is cooled by temperature-controlled fan
 - Control via RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; sound to light via microphone
 - Preprogrammed in LED PC-Control 512
 - Flicker-free
 - With a beam angle of 2° - 41°
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x XLR cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	7 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
Equipment:	Zoom motor driven
DMX channels:	18; 19; 20; 50
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; sound to light via microphone
Preprogrammed in:	LED PC-Control 512
Projection:	Flicker-free
Beam angle:	2° - 41°
Beam angle (1/2 peak):	2 - 23°
Beam angle (1/10 peak):	6 - 41°
Illuminance in Lux (lx):	Narrow red (R) 3m: 1197 lx, 6m: 329 lx

Narrow green (G) 3m: 3225 lx, 6m: 824 lx
Narrow blue (B) 3m: 560 lx, 6m: 144 lx
Narrow cold white (CW) 3m: 3792 lx, 6m: 976 lx
Narrow all 3m: 7966 lx, 6m: 2056 lx
Wide red (R) 3m: 82 lx, 6m: 23 lx
Wide green (G) 3m: 230 lx, 6m: 61 lx
Wide blue (B) 3m: 40 lx, 6m: 11 lx
Wide cold white (CW) 3m: 266 lx, 6m: 72 lx
Wide all 3m: 559 lx, 6m: 151 lx

Housing color:	Black
Dimensions:	Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm
Weight:	6,00 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting