

FUTURELIGHT EYE-108 Moving-Head Wash

Moving Head wash with 3 W Luxeon Rebel RGBW LEDs

Art. No.: 51841339

GTIN: 4026397383232



The article is no longer in our assortment.

Features:

- Equipped with 108 x 3 W high power LEDs "Luxeon Rebel" made by Lumileds, USA
- LEDs: 52 x red, 22 x green, 22 x blue, 12 x white
- Correction of the color temperature via 12 cold white LEDs possible
- Luxeon Rebel LEDs have a very high brightness and extreme long life
- Long LED life
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link (from software version 2.0, 06/2010)
- Sound-controlled via built-in microphone
- Exact positioning via 16-bit Pan/Tilt movement resolution
- PAN angle switchable between 630° and 540°
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Stepless RGBW color changing
- Programmable color change speed and strobe effect
- Random strobe effect
- Lightbeam with 40° radiation angle
- Blue LCD display
- Upgrade via further optional module: wireless receiver for W-DMX operation
- ESDC function (Easy Service Data Check) with battery-buffered Control Board for operation time readouts etc.

Logistic

EAN / GTIN: 4026397383232
Weight: 11,35 kg
Length: 0.47 m
Width: 0.35 m
Height: 0.43 m

- Strobe effect with 1-25 flashes per second
- Masterdimmer
- Rainbow effect
- Control Board with LCD display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt Reverse, Program, Reset
- RDMX (Remote DMX Addressing): DMX address setting via controller possible
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via every standard DMX controller

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	340,00 W
Dimensions:	Width: 32,5 cm Depth: 44,5 cm Height: 23 cm
DMX channels:	13
DMX connection:	3-pin XLR
Flash-rate:	25 Hz
Maximum PAN-movement 630°:	in 2.5 s
Maximum TILT-movement 265°:	in 1.5 s
LED number:	108
Beam angle:	40°
Dimensions (L x W x H):	325 x 230 x 445 mm
Weight:	10 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting