

FUTURELIGHT Stage Pixel Bar 10 WW

High performance LED bar with 17 W white light LEDs and dim-to-warm function

Art. No.: 51841357 GTIN: 4026397630886









The article is no longer in our assortment.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- 10 powerful LEDs 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
 LEDs controlled separately
- Dimmer curves with adjustable response
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone
- Flicker-free
- With a beam angle of 20°
- Very high color rendering index (CRI)
- With Mounting bracket
- Built with NEUTRIK connector
- For application areas such as: Clubs/dancing school; Stage
- Strobe effect
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- Silent operation
- Mains input and output for power linking up to 8 units

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	185 W

Logistic

EAN / GTIN: 4026397630886

Weight: 11,50 kg Length: 0.97 m Width: 0.25 m Heigth: 0.27 m

Power connection: Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) Power output: 1 x PowerCON (gray), mounting version LED lamp LED: 10 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix) Color temperature: 3000K Flash rate: 0 - 18 Hz DMX channels: 2; 10; 12 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination Intended use: Show effect lighting	IP classification:	IP20
LED lamp LED: LED lamp LED: 10 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix) Color temperature: 3000K Flash rate: 0 - 18 Hz DMX channels: 2; 10; 12 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Network connection: Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light J Projection: Flicker-free Beam angle: 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Power connection:	version power supply cord with safety plug
LED: 10 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix) Color temperature: 3000K Flash rate: 0 - 18 Hz DMX channels: 2; 10; 12 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Network connection: Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light' J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Not designed for household room illumination	Power output:	1 x PowerCON (gray), mounting version
(homogenous color mix) Color temperature: 3000K Flash rate: 0 - 18 Hz DMX channels: 2; 10; 12 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Network connection: Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Lamp type:	LED lamp
Flash rate: DMX channels: 2; 10; 12 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Network connection: Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Not designed for household room illumination	LED:	
DMX input: DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM: ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Beam angle: 20° Beam angle (1/2 peak): 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Not designed for household room illumination	Color temperature:	3000K
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): Color rendering index (CRI): Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Not designed for household room illumination	Flash rate:	0 - 18 Hz
DMX output: 1 x 3-pin XLR (F) mounting version Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light 'J Projection: Flicker-free Beam angle: 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	DMX channels:	2; 10; 12
Network connection: Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	DMX input:	1 x 3-pin XLR (M) mounting version
mounting version Cooling: Passive convection cooling Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	DMX output:	1 x 3-pin XLR (F) mounting version
Control: RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): Color rendering index (CRI): Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Network connection:	· ,
via Microphone Preprogrammed in: LED PC-Control 512; Light Captain; Light'J Projection: Flicker-free Beam angle: 20° Beam angle (1/2 peak): Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Cooling:	Passive convection cooling
Projection: Beam angle: Beam angle (1/2 peak): Color rendering index (CRI): Housing color: Black Attachment system: Use of brands: Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Control:	
Beam angle: 20° Beam angle (1/2 peak): 20° Color rendering index (CRI): 91 Ra Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Preprogrammed in:	LED PC-Control 512; Light Captain; Light J
Beam angle (1/2 peak): Color rendering index (CRI): Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Projection:	Flicker-free
Color rendering index (CRI): Housing color: Black Attachment system: Mounting bracket Use of brands: Built with NEUTRIK connector Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Beam angle:	20°
Housing color: Black Attachment system: Use of brands: Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Beam angle (1/2 peak):	20°
Attachment system: Use of brands: Built with NEUTRIK connector Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Color rendering index (CRI):	91 Ra
Use of brands: Built with NEUTRIK connector Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Dimensions: Length: 87,5 cm Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Attachment system:	Mounting bracket
Depth: 14 cm Height: 18 cm Weight: 9,45 kg Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Use of brands:	Built with NEUTRIK connector
Noise classification: Class 0 (no noise at all) Legal specifications Special product: Not designed for household room illumination	Dimensions:	Depth: 14 cm
Legal specifications Special product: Not designed for household room illumination	Weight:	9,45 kg
Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting