

FUTURELIGHT POS-12 Scan LED QCL

LED color changing bar with TILT movement and 8 W RGBW LEDs (4in1)

Art. No.: 51841363

GTIN: 4026397504569



The article is no longer in our assortment.

Features:

- Stepless vertical movement via control panel or DMX
- Equipped with 12 quadcolor LEDs in the colors red, green, blue and white
- 6, 8, 12 or 54 DMX channels selectable
- Each LED can be controlled individually
- Hanging as well as standing installation possible
- Functions: RGBW color mixture, color presets, 11 preset color temperatures, automatic color change, built-in programs, dimmer, strobe effect, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Automatic position correction
- Sound-controlled via built-in microphone
- Adjustable microphone sensitivity via Control Board
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LCD display and four operating buttons
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Control via DMX
- Preprogrammed in Light'J; LED PC-Control 512

Logistic

EAN / GTIN: 4026397504569

Weight: 6,75 kg

Length: 1.14 m

Width: 0.14 m

Height: 0.26 m

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 140,00 W |
| IP classification: | IP20 |
| Control: | DMX |
| Preprogrammed in: | Light J; LED PC-Control 512 |
| Dimensions: | Length: 1,055 m Depth: 6,6 cm Height: 10,9 cm |
| Weight: | 6,00 kg |
| DMX channels: | 6/8/12/54 |
| DMX connection: | 3-pin XLR |
| Sound-control: | via built-in microphone |
| Flash-rate: | 30 Hz |
| LED type: | 8 W QCL |
| LED number: | 12 |
| Maximum TILT-movement: | 240° |
| Beam angle: | 22° |
| Dimensions (L x W x H): | 1055 x 66 x 109 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |