

FUTURELIGHT DMB-160 LED Moving Head

PRO beam moving-head with 150 W COB LED and many features

Art. No.: 51841807

GTIN: 4026397528657



The article is no longer in our assortment.

Features:

- With glass lens
- Extremely high light output
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 1 powerful LED 150 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN and 270° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; Prism 6-fold Linear; Prism 8-fold rotating; frost filter; Focus motor-driven
- Gobo effect
- Color wheel with 14 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone
- Flicker-free
- With a beam angle of 3°
- Multicolor LCD display
- Dimmer electronic
- Preprogrammed in LED PC-Control 512; Light Captain

Package contents

Logistic

EAN / GTIN: 4026397528657

Weight: 18,05 kg

Length: 0.61 m

Width: 0.44 m

Height: 0.37 m

- 1 x moving light, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x mounting bracket, 1 x xLR cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 150 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Equipment:	Gobo wheel with static gobos; Prism 6-fold Linear; Prism 8-fold rotating; frost filter; Focus motor-driven
Color generation:	Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 17 gobos and open Shake effect
DMX channels:	11; 13; 14; 17
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution upgradeable; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	3°
Beam angle (1/2 peak):	3°
Illuminance in Lux (lx):	Cold white (CW) 3m: 76776 lx, 6m: 18482 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 34,3 cm Depth: 25 cm Height: 42,8 cm
Weight:	15,55 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting
