

FUTURELIGHT DMH-40 LED Moving Head

High performance LED Moving Head

Art. No.: 51841835 GTIN: 4026397420708











The article is no longer in our assortment.

Features:

- 1 extra bright 40 W LED for best luminance
- Comparable to the light output of 250 W discharge lamp
- Effect wheel with rotating 3-facet prism and 3D prism and frost filter
- Macro function for rotating gobos/rotating prism combinations
- Color wheel with 8 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: color change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmei
- Strobe effect with adjustable speed
- Random strobe effect
- Power standby mode
- PAN angle switchable between 630° and 540°
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with 4-digit display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually

Logistic

EAN / GTIN: 4026397420708

Weight: 12,70 kg Length: 0.47 m Width: 0.34 m Heigth: 0.39 m

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- Sound-controlled via built-in microphone
- DMX control via every standard DMX controller
- Control via Sound to light via Microphone; DMX; RDM

Technical specifications:

| <u> </u> | |
|--------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 150 W |
| Flash rate: | 1 - 22 Hz |
| Gobos: | Outside diameter 27mm |
| | Image diameter 22mm |
| DMX channels: | 14 |
| Control: | Sound to light via Microphone; DMX; RDM |
| Beam angle (1/2 peak): | 15° |
| Color: | Black |
| Dimensions: | Length: 30,10 cm |
| Weight: | 11,30 kg |
| DMX channels: | 14 |
| DMX connection: | 5-pin and 3-pin XLR |
| Sound-control: | via built-in microphone |
| Flash-rate: | 22 Hz |
| LED type: | LUMINUS SST-90 |
| LED number: | 1 |
| Beam angle: | 15° |
| Color-wheel: | 8 dichroic filters plus open |
| Rotating gobo-wheel: | 7 gobos and open |
| Outside diameter of the gobos: | 27 mm |
| Image diameter of the gobos: | 22 mm |
| Length of base: | 301 mm |
| Width of yoke: | 247 mm |
| Height (head horizontal): | 406 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |