

FUTURELIGHT DMH-160 LED Moving Head

PRO moving-head with 150 W COB LED and extensive features

Art. No.: 51841971 GTIN: 4026397564228











The article is no longer in our assortment.

Features:

- Equipped with a powerful 150 W COB LED
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution made in Sweden)
- 14, 16, 21 or 24 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Gobo wheel 2 with 7 static gobos plus open
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Autofocus
- Steplessly adjustable iris
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function

Logistic

EAN / GTIN: 4026397564228

Weight: 16,00 kg Length: 0.52 m Width: 0.44 m Heigth: 0.36 m

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- 1 powerful LED 150 W COB (chip-on-board) cold white (CW)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; gobo wheel with static gobos; Iris; Prism 3-fold; Prism 8-fold; Focus motor-driven; frost filter
- Gobo effect; beam effect
- Color wheel with 8 dichroic filters plus open
- Gobo wheel with rotating gobos, 8 gobos and open
gobos changeable
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable
- Preprogrammed in LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 14°

Technical specifications:

100-240 V AC, 50/60 Hz 170 W IP20 Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
IP20 Mains input via PowerCON (blue), mounting version power supply cord with safety plug
Mains input via PowerCON (blue), mounting version power supply cord with safety plug
version power supply cord with safety plug
(ριονίασα)
1 x PowerCON (gray), mounting version
LED lamp
1 x 150 W COB (chip-on-board) cold white (CW)
270° Exact positioning (16 bit resolution) Auto position correction (feedback)
540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Gobo wheel with rotating gobos; gobo wheel with static gobos; Iris; Prism 3-fold; Prism 8-fold; Focus motor-driven; frost filter
Color wheel with 8 dichroic filters plus open
Gobo wheel with rotating gobos, 8 gobos and open
Outside diameter 28mm
Image diameter 22mm
Gobos changeable
14; 16; 21; 24
Temperature-controlled fan
Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable
LED PC-Control 512; Light Captain
Flicker-free

Beam angle:	14°
Beam angle (1/2 peak):	14°
Illuminance in Lux (lx):	Cold white (CW) 3m: 14068 lx, 6m: 3617 lx
Housing color:	Black
Dimensions:	Width: 34,3 cm Depth: 25 cm Height: 42,8 cm
Weight:	14,05 kg
DMX channels:	14/16/21/24
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
LED type:	150 W COB
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Static gobo-wheel:	7 gobos and open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting