

FUTURELIGHT PRO Slim PAR-12 MK2 HCL

Flat PRO LED spotlight with 12 x 10 W 6in1 LED (RGBWA+UV) without fan

Art. No.: 51842561

GTIN: 4026397590609



The article is no longer in our assortment.

Features:

- Equipped with 12 high-power LEDs in the colors red, green, blue, amber, white and UV
 - Flat housing form requires minimal space when rigging
 - Extremely compact housing in a beautiful design
 - Second mounting bracket for safe standing installation
 - Locking possibility at the brackets with large metal butterfly screws
 - Functions: static colors, RGBWA+UV color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation
 - Addressing and setting via Control Board with four operating buttons and LED display
 - Switch-mode power supply for operation between 100 and 240 volts
 - P-Con terminals for power linking up to 8 units
 - 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
 - Strobe effect; UV effect
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; Sound to light via Microphone
 - Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
 - Flicker-free
 - With a beam angle of 18°
 - Silent operation
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397590609
Weight: 5,40 kg
Length: 0.26 m
Width: 0.26 m
Height: 0.31 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	32°
Housing color:	Black
Dimensions:	Width: 28 cm Depth: 12,5 cm Height: 29,5 cm
Weight:	4,80 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting