

FUTURELIGHT PRO Slim PAR-6 COB RGB

PRO slimline LED spot with 6 x 30 W COB (RGB) without fan

Art. No.: 51842564 GTIN: 4026397651577











The article is no longer in our assortment.

Features:

- 6 high-power 30 W COB LEDs (3in1)
- Flat version requires minimal space when mounting
- Compact design
- Additional bracket for floor use
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Fuzzy sound control: program continues automatically during periods without music or bassbeat
- Control panel with LED display for easy configuration
- Mains input and output for power linking up to 8 units
- 6 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; Sound to light via Microphone; Master/slave function
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4;
 LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 36°
- With Mounting bracket
- Silent operation

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397651577

Weight: 5,50 kg Length: 0.26 m Width: 0.26 m Heigth: 0.31 m

Technical specifications:

| - common opcomonations | |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 115 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Lamp type: | LED lamp |
| LED: | 6 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix) |
| DMX channels: | 3; 5; 7 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; Sound to light via Microphone; Master/slave function |
| Preprogrammed in: | Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 36° |
| Beam angle (1/2 peak): | 36° |
| Beam angle (1/10 peak): | 80° |
| Housing color: | Black |
| Attachment system: | 2x Mounting bracket |
| Dimensions: | Width: 28,7 cm Depth: 12,6 cm Height: 30 cm |
| Weight: | 5,07 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |