

FUTURELIGHT SVS-37.5 LED display 90x90

LED video display for outdoor use

Art. No.: 51843210

GTIN: 4026397465334



The article is no longer in our assortment.

Features:

- Modular LED video display for outdoor use, IP63
- Extra bright and colorful projection of videos, animations and graphics
- Ideal for rental companies, stage/fair construction and fixed installation
- Super-light and durable aluminum construction
- Seamless, modular display concept allows the build-up of large areas
- 37.5 mm pixel pitch
- 1024 pixels (32 x 32)
- Supports full HD 1080p
- Signal processing via onboard receiver card
- Control via optional video processor or PC software
- Ethernet-based signal distribution
- Truss support bar, signal and power cables optional

Logistic

EAN / GTIN: 4026397465334

Weight: 22,00 kg

Length: 1.01 m

Width: 0.22 m

Height: 1.02 m

Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180,00 W
IP classification:	IP63
Dimensions:	Width: 90 cm Height: 90 cm
Weight:	17,05 kg
Resolution (W x H):	32 x 32 pixels

Pixel pitch:	37.5 mm
Pixel density:	711/m ²
Pixel configuration:	DIP346
Signal connection:	DVI/RJ45
Display mode:	progressive scan
Brightness:	3300 cd/m ² (nits)
Viewing angle:	50° horizontally 110° vertically
Data refresh rate:	>2400 Hz
Contrast level:	>8192
Grey scale:	16 bits
Number of displays:	max. 1280 per sending card up to 1280 x 1024 pixels
Protection grade:	IP63
Operating temperature:	-10 to 45 °C
Humidity:	10 to 95 %
Dimensions:	900 x 900 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting