

## EUROLITE LED PS-4 HCL Spot

Compact, fanless spot with 12 W 6in1 LEDs (RGBWA+UV)

Art. No.: 51913503

GTIN: 4026397556285



**The article is no longer in our assortment.**

### Features:

- Operable in stand-alone mode or via DMX
  - Adjustable microphone sensitivity via control board
  - Functions: Static colors, RGBAW+UV color mixture, UV effects, auto mode, internal programs, dimmer and strobe settings via DMX, Master/Slave
  - Equipped with 4 x 12 W LEDs in red, green, blue, amber, white and UV
  - Designed for hanging or standing installation
  - Comfortable addressing and setting via control board with LED display and four operating buttons
  - Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
  - IEC terminals for power linking up to 8 units
  - Switch-mode power supply for operation between 100 and 240 volts
  - 4 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
  - Strobe effect; UV effect
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone
  - Preprogrammed in Light´J; LED PC-Control 512; Light Captain
  - With a beam angle of 23°
  - Silent operation
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397556285  
Weight: 2,00 kg  
Length: 0.23 m  
Width: 0.20 m  
Height: 0.17 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	33 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	4 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Beam angle:	23°
Beam angle (1/2 peak):	23°
Beam angle (1/10 peak):	42°
Housing color:	Black
Dimensions:	Width: 18,9 cm Depth: 11,7 cm Height: 19,6 cm
Weight:	1,78 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting