

EUROLITE Stage Panel 16 QCL RGB/WW LED

LED light effect bar with RGB/WW color mixing

Art. No.: 51913892

GTIN: 4026397718256



List price: 474.81 €

incl. 19% VAT.

Features:

- 16 powerful LEDs 7 W SMD 4in1 QCL RGB/WW (homogenous color mix)
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; Sound to light via Microphone; Master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); IR remote control
- Flicker-free
- With a beam angle of 15°
- With Mounting bracket
- 4 digit 7-segment LED display
- 4 pixel groups for dynamic running light effects
- 4 barn doors to avoid blinding the audience and for protection during transport
- Preprogrammed in Light Captain; Colorchief; EASY SHOW 2; EASY SHOW 3; Light J
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; Installation; Stage; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x barn door, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397718256

Weight: 5,80 kg

Length: 0.56 m

Width: 0.16 m

Height: 0.24 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	16 x 7 W SMD 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 8; 9; 16; 24
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; Sound to light via Microphone; Master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); IR remote control
Preprogrammed in:	Light Captain; Colorchief; EASY SHOW 2; EASY SHOW 3; Light J
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 52,5 cm Depth: 9,9 cm Height: 18,1 cm
Weight:	5,35 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting