

EUROLITE LED CLS-9 QCL RGB/WW 9x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

Art. No.: 51913901

GTIN: 4026397712841



List price: 272.51 €

incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 3 buttons on the remote control for saving your own settings
- 9 powerful LEDs 7 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Master/slave function; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 10°
- With Mounting bracket
- OLED display
- Silent operation
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; Stage; theater; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x diffusor cover, 1 x remote control, 1 x barndoor, 2 x knurled screw

Logistic

EAN / GTIN: 4026397712841

Weight: 3,50 kg

Length: 0.30 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 54 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray) |
| Lamp type: | LED lamp |
| LED: | 9 x 7 W 4in1 QCL RGB/WW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Master/slave function; Sound to light via Microphone; IR remote control |
| Preprogrammed in: | Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 10° |
| Beam angle (1/2 peak): | 10° Frost filter 18° |
| Beam angle (1/10 peak): | 28° Frost filter 47° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | OLED display |
| Dimensions: | Length: 27,1 cm Width: 14,3 cm Height: 21,3 cm |
| Weight: | 3,20 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |